



**ULTRA HIGH PERFORMANCE**  
**PREMIUM LS665**

- ◆Special asymmetric pattern design provides excellent high speed and handling performance.
- ◆Spiral groove design contributes to outstanding water evacuation and wet grip.
- ◆Special compound design reduces heat generation and enhances grip performance under all road conditions.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD KG LBS	MAX PRESSURE Kpa Psi
185/55R15	82	H	6J	194	585	475/1047	350/51
195/55R15	85	V	6J	201	595	515/1135	350/51
195/45R16	80	V	61/2J	195	582	450/992	350/51
195/55R16	87	V	6J	201	620	545/1201	350/51
195/60R16	89	H	6J	201	640	580/1279	300/44
205/50R16	87	V	61/2J	214	612	545/1201	350/51
205/40ZR17	84XL	W	71/2J	212	596	500/1102	340/50
205/50R17	93XL	V	61/2J	214	638	650/1433	340/50
215/40ZR17	87XL	W	71/2J	218	604	545/1201	340/50
215/45R17	91XL	W	7J	213	626	615/1356	340/50
215/50ZR17	95XL	W	7J	226	648	690/1521	340/50
215/65ZR17	94	W	7J	226	668	670/1477	350/51
225/45R17	94XL	W	7 1/2J	225	634	670/1477	340/50
225/50R17	98XL	V	7J	233	658	750/1653	340/50
225/65ZR17	101XL	W	7J	233	680	825/1819	340/50
235/45R17	97XL	W	8J	236	644	730/1609	340/50
235/50ZR17	96	W	71/2J	245	668	710/1565	350/51
235/65ZR17	99	W	71/2J	245	690	775/1709	350/51
215/35ZR18	84XL	W	71/2J	218	607	500/1102	340/50
225/40R18	92XL	W	8J	230	637	630/1389	340/50
225/45ZR18	95XL	W	7 1/2J	225	659	690/1521	340/50
235/40ZR18	95XL	W	81/2J	241	645	690/1521	340/50
235/45ZR18	98XL	W	8J	236	669	750/1653	340/50
245/40ZR18	97XL	W	8 1/2J	248	653	730/1609	340/50
245/45ZR18	100XL	W	8J	243	677	800/1764	340/50
255/35ZR18	94XL	W	9J	260	635	670/1477	340/50
245/35R20	95XL	W	8 1/2J	248	680	690/1521	340/50



**QINGDAO MYHWAY INTERNATIONAL TRADE CO LTD**

**ADD: NO.39 SHILING ROAD, QINGDAO CITY, SHANDONG, CHINA**

**Email: rambo@myhway.com**

**Mob: 0086-15069105211**

**Web: www.myhway.com**



**SEMI-STEEL RADIAL TIRE**



**HIGH PERFORMANCE**  
**COMFORT ES655**

- ◆Four grooves with open shoulder provides perfect water evacuation.
- ◆Center rib design delivers better straight handling.
- ◆Improved shoulder sipes provide better handling during cornering and low noise emission.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD KG LBS	MAX PRESSURE Kpa Psi
155/65R13	73	T	4 1/2J	157	532	365/805	350/51
155/70R13	75	T	4.50B	157	548	387/853	350/51
155/80R13	79	T	4.50B	157	578	437/963	350/51
165/65R13	77	T	5J	170	544	412/908	350/51
165/70R13	79	T	5.00B	170	562	437/963	350/51
175/70R13	82	T	5.00B	177	576	475/1047	350/51
185/70R13	86	T	5 1/2J	189	590	530/1168	350/51
155/65R14	75	T	4 1/2J	157	558	387/853	350/51
165/60R14	75	H	5J	170	554	387/853	350/51
165/65R14	79	H	5J	170	570	437/963	300/44
165/70R14	81	T	5J	170	588	462/1018	350/51
175/65R14	82	H	5J	177	584	475/1047	350/51
175/70R14	84	T	5J	177	602	500/1102	350/51
185/60R14	82	H	5 1/2J	189	578	475/1047	350/51
185/65R14	86	H	5 1/2J	189	596	530/1168	350/51
185/70R14	88	T	5 1/2J	189	616	560/1235	350/51
195/60R14	86	H	6J	201	590	530/1168	350/51
195/70R14	91	T	6J	201	630	615/1356	350/51
205/60R14	88	H	6J	209	602	560/1235	300/44
205/70R14	95	H	6J	209	644	690/1521	350/51
215/70R14	96	H	6 1/2J	221	658	710/1565	350/51
175/65R15	84	H	5J	177	609	500/1102	350/51
185/60R15	84	H	5 1/2J	189	603	500/1102	350/51
185/65R15	88	H	5 1/2J	189	621	560/1235	350/51
195/50R15	82	V	6J	201	577	475/1047	350/51
195/55R15	85	V	6J	201	595	515/1135	350/51
195/60R15	88	H	6J	201	615	560/1235	350/51
195/65R15	91	H	6J	201	635	615/1356	350/51
205/60R15	91	H	6J	209	627	615/1356	350/51
205/65R15	94	H	6J	209	647	670/1477	350/51
205/70R15	96	T	6J	209	669	710/1565	350/51
215/70R15	98	T	6 1/2J	221	683	750/1653	350/51
225/70R15	100	H	6 1/2J	228	697	800/1764	300/44
205/45R16	83	H	7J	206	590	487/1073	350/51
205/55R16	91	V	6 1/2J	214	632	615/1356	350/51
205/60R16	92	H	6J	209	652	630/1389	350/51
215/55R16	93	V	7J	226	642	650/1433	350/51
215/60R16	95	H	61/2J	221	664	690/1521	350/51
225/50R16	92	V	7J	233	632	630/1389	350/51
225/55R16	95	V	7J	233	654	690/1521	350/51
225/60R16	98	H	61/2J	228	676	750/1653	350/51





**HT TIRE**

**PREMIUM LS667**

- ◆ Four wide longitudinal water-escaping grooves and spacious transverse water-escaping grooves water to improve water dispersion for excellent traction and braking on wet roads. Powerful with the luxurious SUV-oriented UHP tyre.
- ◆ Outstanding performance on all roads with the wide tread and high groove-speration. Tranquil ride with the ideal pitch design and the variable sound frequency blocks. Special quality with good performance on anti-puncture, underlay-damage and anti-friction from the unique sidewall protection layer.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD KG LBS	MAX PRESSURE Kpa Psi
285/50R20	116XL	V	9J	297	794	1250/2756	340/50



**HIGH PERFORMANCE**

**COMFORT ES656**

- ◆ Special compound design ensures a long mileage.
- ◆ The combination of blocks provides a superior driving performance and a strong grip.
- ◆ Three main grooves contribute to better water drainage and wet traction.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD KG LBS	MAX PRESSURE Kpa Psi
175/70R14	84	T	5J	177	602	500/1102	300/44
185/60R14	82	H	5.5J	189	578	475/1047	300/44
185/65R15	88	H	5.5J	189	621	560/1235	300/44
195/60R14	86	H	6J	201	590	530/1168	300/44
205/65R15	94	H	6J	209	647	670/1477	300/44



**COMMERCIAL LIGHT TRUCK**

**HIGHLANDER LX755**

- ◆ Special compound design ensures a long mileage.
- ◆ The combination of blocks provides a superior driving performance and a strong grip.
- ◆ Three main grooves contribute to better water drainage and wet traction.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD SINGLE KG LBS	*MAX LOAD DUAL KG LBS*	MAX PRESSURE Kpa Psi
155R13C	90/88	Q	4.50B	157	578	600/1323	560/1235	450/65
165R13C	94/93	R	4.50B	165	594	670/1477	650/1433	450/65
175R13C	97/95	R	5.00B	177	610	730/1609	690/1521	450/65
185R14C	102/100	Q	5 1/2J	189	652	850/1875	800/1765	450/65
195R14C	106/104	Q	5 1/2J	196	668	950/2095	900/1985	450/65
185R15C	103/102	Q	5 1/2J	189	677	875/1930	850/1875	450/65
195/70R15C	104/102	Q	6J	201	655	900/1984	850/1874	450/65
195R15C	106/104	R	5 1/2J	196	693	950/2094	900/1984	450/65
175R16C	101/99	Q	5J	178	684	825/1819	775/1709	450/65
185/75R16C	104/102	S	5J	184	684	900/1985	850/1875	475/70



**COMMERCIAL LIGHT TRUCK**

**HIGHLANDER LX756**

- ◆ Special compound design ensures a long mileage.
- ◆ The combination of blocks provides a superior driving performance and a strong grip.
- ◆ Three main grooves contribute to better water drainage and wet traction.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD SINGLE KG LBS	*MAX LOAD DUAL KG LBS*	MAX PRESSURE Kpa Psi
175/70R14C	95/93	S	5J	177	602	690/1521	650/1433	375/54
225/65R16C	112/110	T	6 1/2J	228	698	1120/2469	1060/2337	475/69
235/65R16C	115/113	R	7J	240	712	1215/2679	1150/2535	475/69



**HT TIRE**

**PREMIUM LS668**

- ◆ Four wide longitudinal water-escaping grooves and spacious transverse water-escaping grooves water to improve water dispersion for excellent traction and braking on wet roads. Powerful with the luxurious SUV-oriented UHP tyre.
- ◆ Outstanding performance on all roads with the wide tread and high groove-speration. Tranquil ride with the ideal pitch design and the variable sound frequency blocks. Special quality with good performance on anti-puncture, underlay-damage and anti-friction from the unique sidewall protection layer.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD KG LBS	MAX PRESSURE Kpa Psi
235/75R15	105	S	6 1/2J	235	733	925/2039	300/44
215/65R16	102XL	H	6 1/2J	221	686	850/1874	340/50
215/70R16	100	T	6 1/2J	221	708	800/1764	300/44
225/70R16	103	T	6 1/2J	228	722	875/1929	300/44
235/60R16	100	H	7J	240	688	800/1764	300/44
255/70R16	111	H	7 1/2J	260	784	1090/2403	300/44
215/60R17	96	H	6 1/2J	221	690	710/1565	300/44
225/60R17	99	V	6 1/2J	228	702	775/1709	300/44
225/65R17	102	V	6 1/2J	228	724	850/1874	300/44
235/65R17	108XL	H	7J	240	738	1000/2205	340/50
245/65R17	107	H	7J	248	750	975/2149	300/44
285/65R17	112	H	8J	272	776	1120/2469	300/44
285/70R17	115	S	8J	272	804	1215/2679	300/44
215/55R18	95	V	7J	226	693	690/1521	300/44
235/55R18	100	V	7 1/2J	245	715	800/1764	300/44
235/65R18	106	H	7J	240	763	950/2094	300/44
265/70R18	116	S	8J	272	829	1250/2756	300/44
225/55R19	99	V	7J	233	731	775/1709	300/44
235/65R19	105XL	V	7 1/2J	245	741	925/2039	340/50
245/65ZR19	103	W	7 1/2J	253	753	875/1929	300/44



**SUV/LIGHT TRUCK**

**HIGHLANDER LX757**

- ◆ Wide-angle lateral grooves ensure excellent on-and-off road performance.
- ◆ Unique pattern design reduces noise generation, improves driving stability and wet grip performance.
- ◆ Optimized tread compound contributes to good durability, good driving comfort, high traction on both dry and wet grounds.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD SINGLE KG LBS	*MAX LOAD DUAL KG LBS*	MAX PRESSURE Kpa Psi
215/75R15	100	S	6J	216	703	800/1764	-/-	350/50
225/70R15C	112/110	R	6 1/2J	228	697	1120/2470	1060/2335	450/65
225/75R15	106XL	S	6J	223	719	950/2094	-/-	340/50
LT235/75R15	110/107	S	6 1/2J	235	733	1060/2335	975/2150	450/65
205/80R16	104XL	T	5 1/2J	203	734	900/1984	-/-	340/50
235/65R16C	115/113	R	7J	240	712	1215/2679	1150/2535	475/69
235/70R16	106	T	7J	240	736	950/2094	-/-	350/51
LT245/75R16	120/116	Q	7J	248	774	1380/3042	1260/2778	550/80
245/70R16	111XL	T	7J	248	750	1090/2403	-/-	340/50
265/70R16	112	T	8J	272	778	1120/2469	-/-	350/51
225/60R17	99	H	6 1/2J	228	702	775/1709	-/-	350/51
225/65R17	102	H	6 1/2J	228	724	850/1874	-/-	350/51
235/60R18	107XL	H	7J	240	739	975/2149	-/-	340/50



**WINTER TIRE**

**NOVA BREAKER 855**

- ◆ Serrated design in the outside main groove assures high grip and braking force on ICE and SNOW covered surfaces.
- ◆ Deep and densely distributed grooves and steel sheet helps soften the tread, contributes to shorten braking distance on ice covered surface.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD KG LBS	MAX PRESSURE Kpa Psi
155/65R13	73	T	4 1/2J	157	532	365/805	350/51
165/70R13	79	T	5.00B	170	562	437/963	350/51
175/70R13	82	T	5.00B	177	576	475/1047	350/51
175/65R14	82	T	5J	177	584	475/1047	350/51
175/70R14	84	T	5J	177	602	500/1102	300/44
185/60R14	82	T	5 1/2J	189	578	475/1047	350/51
185/65R14	86	T	5 1/2J	189	596	530/1168	350/51
185/70R14	88	T	5 1/2J	189	616	560/1235	300/44
185/60R15	84	T	5 1/2J	189	603	500/1102	350/51
195/60R15	88	T	6J	201	615	560/1235	350/51
185/65R15	88	T	5 1/2J	189	621	560/1235	300/44
195/55R15	85	T	6J	201	595	515/1135	300/44
195/65R15	91	T	6J	201	635	615/1356	350/51
205/65R15	94	T	6J	209	647	670/1477	350/51
205/55R16	91	H	6 1/2J	214	632	615/1356	350/51
205/60R16	92	T	6J	209	652	630/1389	350/51
215/60R16	95	T	6 1/2J	221	664	690/1521	350/51
225/60R16	98	T	6 1/2J	228	676	750/1653	350/51
205/50R17	89	H	6 1/2J	214	638	580/1279	350/51
225/45R17	91	H	7 1/2J	225	634	615/1356	350/51
215/55R17	94	T	7J	226	668	670/1477	300/44
225/55R17	97	T	7J	233	680	730/1609	300/44
215/60R17	96	T	6 1/2J	221	690	710/1565	300/44
225/60R17	99	T	6 1/2J	228	702	775/1709	300/44
225/65R17	102	T	6 1/2J	228	724	850/1874	300/44
215/55R18	95	T	7J	226	693	690/1521	300/44
225/60R18	100	T	6 1/2J	228	727	800/1764	300/44
245/55R19	103	T	7 1/2J	253	753	875/1929	300/44