



QINGDAO MYHWAY INTERNATIONAL TRADE CO LTD  
ADD: NO.39 SHILING ROAD, QINGDAO, SHANDONG, CHINA

Email: rambo@myhway.com  
Mob: 0086-15069105211  
Web: www.myhway.com



## ZA156 ALL POSITION

### HIGH MILEAGE / STONE-PROOF / HIGH WEAR RESISTANCE

- ◆ Three longitudinal zigzag pattern groove design, V-shaped groove design prevent stone clamping.
- ◆ Transverse steel groove design, excellent handling and comprehensive performance.
- ◆ Wave groove and anti-clamping stone design, excellent self-cleaning performance.

Size	PR	Load Index Single/Dual	Speed Symbol	Standard Rim	Section Width (mm)	Max Load(kg)		Max Pressure(kpa)	
						Single	Dual	Single	Dual
12R22.5	18	152/149	L	9.00	300	3550	3250	930	930
		154/151	L	9.75	320	3750	3450	830	830
13R22.5	20	157/154	K	9.75	320	4125	3750	900	900



## ZD158 DRIVE

### HIGH MILEAGE/STONE-PROOF/HIGH WEAR RESISTANCE

- ◆ Mixed pattern design provide strong traction and breaking power.
- ◆ Super abrasion resistance, excellent heat dissipation performance.
- ◆ Good handing and traction with higher original mileage.
- ◆ Excellent fuel efficiency.

Size	PR	Load Index Single/Dual	Speed Symbol	Standard Rim	Section Width (mm)	Max Load(kg)		Max Pressure(kpa)	
						Single	Dual	Single	Dual
12R22.5	18	152/149	K	9.00	300	3550	3250	930	930
		154/151	K	9.75	320	3750	3450	830	830
13R22.5	20	157/154	J	9.75	320	4125	3750	900	900
295/80R22.5	18	152/149	L	9.00	298	3550	3250	900	900
315/80R22.5	20	157/154	L	9.00	312	4125	3750	900	900



## ZD159 DRIVE

### HIGH MILEAGE / HIGH WEAR RESISTANCE / STRONG GRIP

- ◆ Deepened groove and wide surface design improve driving range.
- ◆ Mixed pattern design provided strong traction and breaking power.
- ◆ Widen tread design improve pattern saturation and higher original mileage.

Size	PR	Load Index Single/Dual	Speed Symbol	Standard Rim	Section Width (mm)	Max Load(kg)		Max Pressure(kpa)	
						Single	Dual	Single	Dual
12R22.5	18	152/149	L	9.00	300	3550	3250	930	930
		152/149	L	9.00	298	3550	3250	900	900
315/80R22.5	20	157/154	L	9.00	312	4125	3750	900	900



## ZD160 DRIVE

### HIGH MILEAGE / STRONG GRIP

- ◆ Deepened groove and wide surface design improve driving range.
- ◆ Mixed pattern design provided strong traction and breaking power.
- ◆ Widen tread design improve pattern saturation and higher original mileage.

Size	PR	Load Index Single/Dual	Speed Symbol	Standard Rim	Section Width (mm)	Max Load(kg)		Max Pressure(kpa)	
						Single	Dual	Single	Dual
12R22.5	18	152/149	L	9.00	300	3550	3250	930	930



## ZD169 MINING

### HIGH WEAR RESISTANCE / ANTI-PUNCTURED

- ◆ Super deepened pattern groove design, ultra high service life.
- ◆ Continuous large block pattern design, cutting resistance, explosion proof.
- ◆ Special mine cutting resistance formula, anti-puncture.

Size	PR	Load Index Single/Dual	Speed Symbol	Standard Rim	Section Width (mm)	Max Load(kg)		Max Pressure(kpa)	
						Single	Dual	Single	Dual
12R22.5	18	152/149	J	9.00	300	3550	3250	930	930



## ZD980 DRIVE

### LOW HEAT GENERATION / HIGH WEAR RESISTANCE

- ◆ The air column design reduces crown cavitation and prolongs service life.
- ◆ Special mine cutting resistance formula, cutting resistance, anti-puncture
- ◆ Reinforcing bars design increases the rigidity of the crown and improves the impact resistance.

Size	PR	Load Index Single/Dual	Speed Symbol	Standard Rim	Section Width (mm)	Max Load(kg)		Max Pressure(kpa)	
						Single	Dual	Single	Dual
12.00R20	20	156/153	F	8.5	315	4000	3650	900	900



## ZD625K DRIVE

### STONE-PROOF / HIGH WEAR RESISTANCE

- ◆ Deepen the pattern groove, increase the width of driving surface, and provide ultra-high service life of the tire.
- ◆ New high-strength tire steel wire improves impact resistance and driving safety.

Size	PR	Load Index Single/Dual	Speed Symbol	Standard Rim	Section Width (mm)	Max Load(kg)		Max Pressure(kpa)	
						Single	Dual	Single	Dual
12.00R20	20	156/153	J	8.5	315	4000	3650	900	900



## ZD616 DRIVE

### HIGH WEAR RESISTANCE / STRONG GRIP

- ◆ Mixed deep groove designed for higher driving range.
- ◆ The large area pattern blocks provide strong power and maintain high gripping power on both wet and dry roads.
- ◆ Shoulder incision design, prevent irregular wear, high heat dissipation.

Size	PR	Load Index Single/Dual	Speed Symbol	Standard Rim	Section Width (mm)	Max Load(kg)		Max Pressure(kpa)	
						Single	Dual	Single	Dual
11R22.5	16	146/143	L	8.25	279	3000	2725	830	830



## ZD788 DRIVE

### STONE-PROOF / STRONG GRIP

- ◆ Widen tread width design provides excellent driving and gripping power.
- ◆ Extra deep tread provides an extra powerful traction and long tread life.
- ◆ Closed shoulder maintains good irregular wear resistance, excellent crack and tear resistance performance.

Size	PR	Load Index Single/Dual	Speed Symbol	Standard Rim	Section Width (mm)	Max Load(kg)		Max Pressure(kpa)	
						Single	Dual	Single	Dual
11R22.5	16	146/143	L	8.25	279	3000	2725	830	830
11R24.5	16	149/146	L	8.25	279	3250	3000	830	830



## ZD690 MINING

### HIGH WEAR RESISTANCE / STONE-PROOF / STRONG GRIP

- ◆ The enhance rubber compound improves cut and chunking resistance.
- ◆ Reinforced belt and body construction enhance the loading ability.
- ◆ The aggressive multi-lug design provides exceptional off-road traction.

Size	PR	Load Index Single/Dual	Speed Symbol	Standard Rim	Section Width (mm)	Max Load(kg)		Max Pressure(kpa)	
						Single	Dual	Single	Dual
11R22.5	16	146/143	L	8.25	279	3000	2725	830	830
12.00R24	20	160/157	L	8.5	315	4500	4125	900	900
295/80R22.5	18	152/149	L	9.00	298	3550	3250	900	900



## ZA750 TRAILER

### LOW HEAT GENERATION / HIGH WEAR RESISTANCE

- ◆ Suitable for truck and bus wheel position, all-weather and all-road driving, small rolling resistance, low heating, wear resistance and fuel saving.
- ◆ Wide section design, superior safety and ride comfort.

Size	PR	Load Index Single/Dual	Speed Symbol	Standard Rim	Section Width (mm)	Max Load(kg)		Max Pressure(kpa)	
						Single	Dual	Single	Dual
385/65R22.5	20	160	K	11.75	389	4500	-	900	-



TBR TIRE  
All Steel Radial Tyre

